


Naaldhulslager GBRI446832-IKO - GBRI446832-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri446832-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
69.850 (2 3/4)	GBRI 446832	1 840	69.850 (2 3/4)	107.950 (4 1/2)	50.800 (2)	51.050	82.550 (3 1/2)

Standard mounting dimensions mm		Basic dynamic load C _r (*) N	Limiting load rating C _L N	Allowable rotational speed (**) rpm	Assembled inner ring
d _a Min.	D _a Max.				
77	79	214 000	452 000	1 800	LRBZ 445232

Notes: (*) Maximum permissible corner radius of the housing.
(**) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377964
Binnendiameter	69.85 mm
Buitendiameter	107.95 mm
Dikte	50.8 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE