


Naaldhulslager GBRI608432-IKO - GBRI608432-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri608432-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
95.250 (3 3/4)	GBRI 608432	2 380	95.250 (3 3/4)	133.350 (5 1/4)	50.800 (2)	51.050	107.950 (4 1/4)

Standard mounting dimensions mm				Basic dynamic load rating <i>C</i> N	Static load rating <i>C₀</i> N	Allowable rotational speed (F) rpm	Assembled inner ring
<i>d_a</i>	<i>D_a</i>	<i>r_a</i> max	<i>r_{as}</i> max (*)				
Min. 103	Max. 105	125.3	1.5	242 000	590 000	1 400	LRBZ 606832

Notes: (*) Maximum permissible corner radius of the housing.
(F) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952378008
Binnendiameter	95.25 mm
Buitendiameter	133.35 mm
Dikte	50.8 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE