

Naaldhulslager RNA4902-U-IKO - RNA4902-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna4902-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|--|----------------------------------|-----------------------------------|--------------------------------|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_s (1) |
| 20 | --- | RNA 4902U | --- | --- | 21.5 | 20 | 28 | 13 | 0.3 |
| Standard mounting diameter D_s Max. mm | Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed (2) | | | | | | |
| 26 | 9 570 | 11 600 | 9 500 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952378855 |
| Binnendiameter | 20 mm |
| Buitendiameter | 28 mm |
| Dikte | 13 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE