

Naaldhulslager RNA6902-U-IKO - RNA6902-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna6902-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)	
20	---	---	---	---	RNA 6902U	37.5	20	28	23	0.3

Standard rounding dimension D_2 Max. mm	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (1) (2)
26	18 500	27 100	9 500 rpm

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952378886
Binnendiameter	20 mm
Binnendiameter	0.787" inch
Buitendiameter	28 mm
Buitendiameter	1.102" inch
Dikte	23 mm
Dikte	0.906" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE