

## Naaldhulslager RNA6908-U-IKO - RNA6908-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna6908-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	D	C	$r_s$ (1)
48	—	—	—	RNA 6908U	270	48	62	40	0.6
Standard mounting dimension $D_s$ Max. mm									
	Basic dynamic load rating C	Basic static load rating $C_0$	Allowable hydraulic speed (2)						
	58	63 700	117 000	4 000					

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379265
Binnendiameter	48 mm
Buitendiameter	62 mm
Dikte	40 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE