

Naaldhulslager RNA49-52-U-IKO - RNA49-52-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna49-52-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
60	—	RNA 49/52U	—	—	200	60	75	22	0.6
Standard rounding dimension D_s Max. mm		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (reference speed) rpm					
71		42 100	73 600	3 000					

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379395
Binnendiameter	60 mm
Buitendiameter	75 mm
Dikte	22 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE