

Naaldhulslager RNA6912-UU-IKO - RNA6912-UU-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna6912-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_1 (1)
68	—	—	RNA6912UU	—	505	68	85	45	1
Standard mounting dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (1)						
	N	N	rpm						
	80	93 400	186 000	3 000					

Notes: (1) Minimum allowable value of chamfer dimension r . Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379500
Binnendiameter	68 mm
Binnendiameter	2.677" inch
Buitendiameter	85 mm
Buitendiameter	3.346" inch
Dikte	45 mm
Dikte	1.772" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE