

# Naaldhulslager RNA4916-U-IKO - RNA4916-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna4916-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
90	---	<b>RNA 4916U</b>	---	---	545	90	110	30	1
Standard rounding dimension $D_s$ Max. mm									
	Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed (2) rpm						
105	80 700	158 000	2 000						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379685
Binnendiameter	90 mm
Buitendiameter	110 mm
Dikte	30 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE