

# Naaldhulslager RNA6917-U-IKO - RNA6917-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna6917-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	D	C	$r_s$ (1)
100	—	—	—	RNA 6917U	1 300	100	120	63	1.1
Standard mounting dimension $D_s$ Max. mm									
	Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed (1) (2)						
	N	N	rpm						
	113.5	168 000	448 000	1 900					

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379760
Binnendiameter	100 mm
Buitendiameter	120 mm
Dikte	63 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE