

Naaldhulslager RNA4926-UU-IKO - RNA4926-UU-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/rna4926-uu-iko



MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
150	RNA 4926UU	—	—	—	2 360	150	180	50	1.5
Standard mounting dimension D_A Max. mm	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (1)						
172	206 000	511 000	1 300						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952379913
Binnendiameter	150 mm
Buitendiameter	180 mm
Dikte	50 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE