

## Naaldhulslager NA6901-U-IKO - NA6901-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/na6901-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>12</b>	—	—	—	—	<b>NA 6901U</b>	45.5	12	24	22	23

  

$r_s$ mm	$F_w$	Standard mounting dimensions mm			Basic static load rating $C_0$ N	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring LRTZ 121623
		Min.	Max.	Max.			
0.3	16	14	15	22	15 500	20 400	12 000

Notes: (1) Minimum allowable value of shaft diameter  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952381107
Binnendiameter	12 mm
Buitendiameter	24 mm
Dikte	23 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE