

Naaldhulslager NA6903-U-IKO - NA6903-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/na6903-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
17	—	—	—	—	NA 6903U	68.5	17	30	23	24

r _s min. mm	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.	D _s Max.				
0.3	22	19	21	28	19 800	30 600	8 500	LRTZ 172224

Notes: (1) Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952381206
Binnendiameter	17 mm
Buitendiameter	30 mm
Dikte	24 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE