

Naaldhulslager NA49-32-U-IKO - NA49-32-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/na49-32-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
32	—	NA 49/32U	—	—	167	32	52	20	21

r_s mm (1)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Allowable rotational speed(2) rpm	Assembled inner ring LRTZ 324021
		Min.	Max.	Max.			
0.6	40	36	39	48	29 400	44 200	5 000

Notes: (1) Minimum allowable value of diameter dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952381428
Binnendiameter	32 mm
Buitendiameter	52 mm
Dikte	21 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE