

Naaldhulslager NA6907-U-IKO - NA6907-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/na6907-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
35	—	—	—	—	NA 6907U	320	35	55	36	37

r _s min ⁽¹⁾	F _w	Standard mounting dimensions mm		Basic static load rating C ₀	Basic dynamic load rating C	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.					
0.6	42	39	41	51	51 600	92 600	4 500	LRTZ 354237

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952381473
Binnendiameter	35 mm
Buitendiameter	55 mm
Dikte	37 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE