


## Naaldhulslager NA4915-U-IKO - NA4915-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/na4915-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
<b>75</b>	—	<b>NA 4915U</b>	—	—	815	75	105	30	31

r <sub>s</sub> min <sup>(1)</sup> F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub>	Basic dynamic load rating C <sub>10</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
	Min.	Max.	D <sub>s</sub> Max.					
1	85	80	83	100	79 600	153 000	2 000	LRTZ 758531

Notes: (1) Minimum allowable value of shaft dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952381787
Binnendiameter	75 mm
Buitendiameter	105 mm
Dikte	31 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE