

## Naaldhulslager BR122016-U-IKO - BR122016-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/br122016-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

| Shaft dia.<br>mm<br>(inch)         | Identification number              |                                  | Mass<br>(Ref.)<br>g         | Boundary dimensions mm(inch)              |                           |            |
|------------------------------------|------------------------------------|----------------------------------|-----------------------------|---|---------------------------|------------|
|                                    | With two seals                     | With one seal                    |                             | $F_w$                                     | $D$                       | $C$        |
| <b>19.050</b><br>( $\frac{3}{4}$ ) |                                    | <b>BR 122016 U</b>               | 68                          | 19.050 ( $\frac{3}{4}$ )                  | 31.750 (1 $\frac{1}{4}$ ) | 25.400 (1) |
| Standard mounting dimensions mm    |                                    | Basic dynamic load rating<br>$C$ | Static load rating<br>$C_0$ | Allowable rotational speed <sup>(*)</sup> |                           |            |
| $D_1$<br>Max.                      | $F_{a \text{ max}}$ <sup>(†)</sup> | N                                | N                           | rpm                                       |                           |            |
| 26.5                               | 1.0                                | 20 700                           | 24 400                      | 10 000                                    |                           |            |

Notes: (†) Minimum allowable value of chamfer dimension  $r$ .  
(\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | IKO           |
| N° Ean13       | 3663952382104 |
| Binnendiameter | 19.05 mm      |
| Buitendiameter | 31.75 mm      |
| Dikte          | 25.4 mm       |
| Verpakking     | 1             |

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE