

Naaldhulslager BR162416-U-IKO - BR162416-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/br162416-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
25.400 (1)		BR 162416 U	83	25.400 (1)	38.100 (1 1/2)	25.400 (1)
Standard mounting dimensions mm		Basic dynamic load rating C	Static load rating C_0	Allowable rotational speed ⁽²⁾		
D_1 Max.	r_{as} max	N	N	rpm		
32.9	1.0	23 600	31 300	8 000		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382142
Binnendiameter	25.4 mm
Binnendiameter	1" inch
Buitendiameter	38.1 mm
Buitendiameter	1 1/2" inch
Dikte	25.4 mm
Dikte	1" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE