

Naaldhulslager BR263520-U-IKO - BR263520-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/br263520-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
41.275 (1 1/2)		BR 263520 U	179	41.275 (1 1/2)	55.562 (2 1/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Basic dynamic load rating C	Static load rating C_0	Allowable rotational speed ^(*)		
D_1 Max.	F_{is} max (^(†))	N	N	rpm		
48.3	1.5	44 800	70 900	4 500		

Notes: (*) Minimum allowable value of chamfer dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382258
Binnendiameter	41.275 mm
Buitendiameter	55.562 mm
Dikte	31.75 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE