


## Naaldhulslager BR526828-U-IKO - BR526828-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/br526828-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>82.550</b> (3 1/4)		<b>BR 526828 U</b>	891	82.550 (3 1/4)	107.950 (4 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_4$ Max.	$F_{as}$ max ( <sup>(†)</sup> )	N	N	rpm		
99.7	2.0	109 000	227 000	2 500		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(†) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382418
Binnendiameter	82.55 mm
Buitendiameter	107.95 mm
Dikte	44.45 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE