


## Naaldhulslager BRI61816-U-IKO - BRI61816-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri61816-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		$d$	$D$	$C$	$B$
<b>9.525</b> ( $\frac{3}{8}$ )		<b>BRI 61816 U</b>	78	9.525 ( $\frac{3}{8}$ )	28.575 (1 $\frac{1}{8}$ )	25.400 (1 )	25.650
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring <b>LRBZ 61016 B</b>
	Min.	Max.	Max. as max. <sup>(1)</sup>				
	14	14.5	24.5	18 300	20 000	12 000	

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382470
Binnendiameter	9.525 mm
Buitendiameter	28.575 mm
Dikte	25.4 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE