

## Naaldhulslager BRI142620-U-IKO - BRI142620-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri142620-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>22.225</b> ( $\frac{7}{8}$ )		<b>BRI 142620 U</b>	177	22.225 ( $\frac{7}{8}$ )	41.275 (1 $\frac{3}{4}$ )	31.750 (1 $\frac{1}{4}$ )	32.000
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRBZ 141820 B
	Min.	Max.	Max. as max. <sup>(1)</sup>				
28.575 (1 $\frac{1}{4}$ )	27	27.5	36.0	0.6	34 900	49 900	7 000

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382555
Binnendiameter	22.225 mm
Buitendiameter	41.275 mm
Dikte	31.75 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE