


## Naaldhulslager BRI183020-UU-IKO - BRI183020-UU-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri183020-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		$d$	$D$	$C$	$B$	
<b>28.575</b> (1.125)	<b>BRI 183020 UU</b>		<b>211</b>	<b>28.575</b> (1.125)	<b>47.625</b> (1.875)	<b>31.750</b> (1.250)	<b>32.000</b>	
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min.	Max.	Max. as max. <sup>(*)</sup>					
<b>34.925</b> (1.375)	<b>33.5</b>	<b>33.9</b>	<b>42.4</b>	<b>38 500</b>	<b>60 000</b>	<b>5 500</b>	<b>LRBZ 182220 B</b>	

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382586
Binnendiameter	28.575 mm
Buitendiameter	47.625 mm
Dikte	31.75 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE