


## Naaldhulslager BRI223520-U-IKO - BRI223520-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri223520-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		$d$	$D$	$C$	$B$
<b>34.925</b> (1 3/8)		<b>BRI 223520 U</b>	275	34.925 (1 3/8)	55.562 (2 1/8)	31.750 (1 1/4)	32.000
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min. $d_s$	Max. $D_s$ as max. <sup>(*)</sup>				Min. $r$	Max. $r$
	40.2	40.2	44 800	70 900	4 500	<b>LRBZ 222620 B</b>	

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382630
Binnendiameter	34.925 mm
Buitendiameter	55.562 mm
Dikte	31.75 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE