


## Naaldhulslager BRI243720-UU-IKO - BRI243720-UU-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri243720-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>38.100</b> (1 1/2)	<b>BRI 243720 UU</b>		<b>293</b>	<b>38.100 (1 1/2)</b>	<b>58.738 (2 3/4)</b>	<b>31.750 (1 1/4)</b>	<b>32.000</b>
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
	Min.	Max.	Misg. as max.				
<b>44.450 (1 3/4)</b>	<b>43.3</b>	<b>43.4</b>	<b>51.5</b>	<b>47 500</b>	<b>78 200</b>	<b>4 500</b>	<b>LRBZ 242820 B</b>

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382654
Binnendiameter	38.1 mm
Buitendiameter	58.738 mm
Dikte	31.75 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE