


Naaldhulslager BRI243920-UU-IKO - BRI243920-UU-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri243920-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
38.100 (1 1/2)	BRI 243920 UU		362	38.100 (1 1/2)	61.912 (2 3/4)	31.750 (1 1/4)	32.000
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 243020 B
	Min.	Max.	Misg. as max. ^(*)				
47.625 (1 7/8)	43.3	45	54.7	48 500	82 100	4 000	

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382661
Binnendiameter	38.1 mm
Buitendiameter	61.912 mm
Dikte	31.75 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE