

## Naaldhulslager BRI406028-UU-IKO - BRI406028-UU-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri406028-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>63.500</b> (2 1/2)	<b>BRI 406028 UU</b>		<b>1 065</b>	<b>63.500</b> (2 1/2)	<b>95.250</b> (3 3/4)	<b>44.450</b> (1 3/4)	<b>44.700</b>
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
	Min.	Max.				Min.	Max.
<b>76.200</b> (3 )	<b>71</b>	<b>73</b>	<b>105 000</b>	<b>211 000</b>	<b>2 500</b>	<b>LRBZ 404828 B</b>	

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382777
Binnendiameter	63.5 mm
Buitendiameter	95.25 mm
Dikte	44.45 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE