


Naaldhulslager
GBR324120-U-IKO - GBR324120-U-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr324120-u-iko



MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
50.800 (2)	GBR 324120 UU		255	50.800 1	65.088 2 1/2	31.750 1 1/2
Standard mounting dimensions mm						
D_s Max.	r_{ss} max	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ^(*) rpm		
59.2	1	63 100	130 000	1 600		

Notes^(*) Minimum allowable value of chamfer dimension r

^(*) Allowable rotational speed applies to grease lubrication.

Remark^(*) The outer ring has an oil groove and an oil hole.

2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383064
Binnendiameter	50.8 mm
Buitendiameter	65.088 mm
Dikte	31.75 mm
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE