

Naaldhulslager


GBR526828-UU-IKO - GBR526828-UU-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr526828-uu-iko

IKO

MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (ref.) g	Boundary dimensions mm(inch)		
	With two seals	With (the seal)		F_w	D	C
82.550 (3 1/4)	GBR 526828 UU		960	82.550 3/4	107.950 4/5	44.450 1 1/2
Standard mounting dimensions mm						
D_s	r_{ss} max	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ^(*) rpm		
99.9	1.5	127 000	231 000	950		

Notes^(*)

Minimum allowable value of chamfer dimension r

^(*)

Allowable rotational speed applies to grease lubrication.

Remark^(*)

The outer ring has an oil groove and an oil hole.

2

Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383170
Binnendiameter	82.55 mm
Buitendiameter	107.95 mm
Dikte	44.45 mm
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE