


## Naaldhulslager GBR648032-U-IKO - GBR648032-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr648032-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>101.600</b> (4)	<b>GBR 648032 U</b>		1 380	101.600 (4)	127.000 (5)	50.800 (2)
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball diameter $d_b$	Allowable rotational speed <sup>(*)</sup>		
$D_A$	$r$ as max	N	N	rpm		
119	1.5	182 000	395 000	800		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383231
Binnendiameter	101.6 mm
Buitendiameter	127 mm
Dikte	50.8 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE