

Naaldhulslager GBRI365628-U-IKO - GBRI365628-U-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri365628-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
57.150 (2 1/4)	GBRI 365628 U		1 050	57.150 (2 1/4)	88.900 (3 1/2)	44.450 (1 3/4)

B	F _w	Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	Assembled inner ring	
		d _{min}	d _{max}	D _s Max.					r _{as max} ⁽¹⁾
44.700	69.850 (2 3/4)	65	67	82	1.5	97 200	197 000	1 100	LRBZ 364428

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383545
Binnendiameter	57.15 mm
Buitendiameter	88.9 mm
Dikte	44.45 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE