

Naaldhulslager GBRI122416-UU-IKO - GBRI122416-UU-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri122416-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
19.050 ($\frac{3}{4}$)	GBRI 122416 UU		143	19.050 ($\frac{7}{8}$)	38.100 (1 $\frac{1}{2}$)	25.400 (1)

B	F _w	Standard mounting dimensions - mm			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	D _s Max.				
25.650	25.400 (1)	24	24.4	33.3	31 000	46 100	3 000	LRBZ 121616

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952384610
Binnendiameter	19.05 mm
Buitendiameter	38.1 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE