

Naaldhulslager NAF659530-IKO - NAF659530-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/naf659530-iko>

IKO
NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE
With Inner Ring

| Shaft dia. mm | Identification number | Mass (Ref.) g | Boundary dimensions mm | | | | | Standard mounting dimensions mm | | | | |
|-------------------------------|--------------------------------|---|---------------------------|-----|-----|-----------|-------|---------------------------------|------------|------------|------------|----|
| | | | d | D | C | r_s min | F_w | d_b | D_b Max. | d_b Min. | D_b Max. | |
| 65 | NAF 659530 | 790 | 65 | 95 | 30 | 1.5 | 75 | 82 | 87 | 73 | 73.5 | 76 |
| Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed ⁽¹⁾ | Assembled with inner ring | | | | | | | | | |
| N | N | rpm | LRT 657530 | | | | | | | | | |
| 63 100 | 144 000 | 6 500 | | | | | | | | | | |

Notes:
(1) Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952384832 |
| Binnendiameter | 65 mm |
| Binnendiameter | 2.559" inch |
| Buitendiameter | 95 mm |
| Buitendiameter | 3.74" inch |
| Dikte | 30 mm |
| Dikte | 1.181" inch |
| Gewicht | 790 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE