




Naaldhulslager TRU456430-IKO - TRU456430-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/tru456430-iko>



ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings

NALL49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
45	—	TRU 456430	295	45	64	30	0.6	50.5	58.5
Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm							
32 600	59 700	8 000							

Note(1): Minimum allowable value of chamfer dimension r
 (2): Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952385396
Binnendiameter	45 mm
Buitendiameter	64 mm
Dikte	30 mm
Gewicht	320 g
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE