


Naaldhulslager NAU4916-IKO - NAU4916-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nau4916-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings



NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
80	—	NAU 4916	790	80	110	30	1	89.5	102
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾							
N	N	rpm							
57 200	95 500	4 500							

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952385587
Binnendiameter	80 mm
Buitendiameter	110 mm
Dikte	30 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE