




Naaldhulslager TRU12517860-IKO - TRU12517860-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/tru12517860-iko>



ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings

NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
125	---	TRU 12517860	4 490	125	178	60	1.5	143.5	162
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾							
N	N	rpm							
211 000	408 000	3 000							

Note(1): Minimum allowable value of chamfer dimension r
 (2): Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952385761
Binnendiameter	125 mm
Buitendiameter	178 mm
Dikte	60 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE