


Naaldhulslager NAU4915-UU-IKO - NAU4915-UU-IKO


<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nau4915-uu-iko>



ROLLER BEARINGS

Caged Roller Bearings [With Seal]

Full Complement Roller Bearings [With Seal]



NAU49-UU
TRU-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r _e (1)	J
75	---	NAU 4915UU		750	75	105	30	1	83.5
<i>E_w</i>	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed (1) rpm						
	N	N	2,500						
95.5	54 800	88 200	2,500						

Notes: (1) Minimum allowable value of chamfer dimension r
 (*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386317
Binnendiameter	75 mm
Buitendiameter	105 mm
Dikte	30 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE