


Naaldhulslager NAU4924-UU-IKO - NAU4924-UU-IKO


<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nau4924-uu-iko>



ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**

Full Complement Roller Bearings **[With Seal]**



NAU49-UU
TRU-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r _e (1)	J
120	---	NAU 4924UU		2 680	120	165	45	1.5	136
<i>E_w</i>	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed (1) rpm						
153.5	N	N	1400						

Notes (1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386652
Binnendiameter	120 mm
Buitendiameter	165 mm
Dikte	45 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE