


## Naaldhulslager NAS5012-ZZ-NR-IKO - NAS5012-ZZ-NR-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nas5012-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S	
<b>60</b>		<b>NAS 5012ZZNR</b>	1.20	60	95	99.8	46	45	34	5.5	
	<i>f</i>	<i>c</i>	<i>r</i> mm	<i>J</i>	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm				
	2.5	2	0.6	73	123 000	208 000	1 700				

Notes: (\*) Minimum allowable value of chamfer dimension r.  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386829
Binnendiameter	60 mm
Binnendiameter	2.362" inch
Buitendiameter	95 mm
Buitendiameter	3.74" inch
Dikte	46 mm
Dikte	1.811" inch
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE