


Naaldhulslager NAS5015-UU-NR-IKO - NAS5015-UU-NR-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nas5015-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



NAS50-UUNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
75	NAS 5015UUNR		2.00	75	115	119.5	54	53	42	5.5

f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
2.5	2	0.6	91	179 000	306 000	1 300

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386881
Binnendiameter	75 mm
Buitendiameter	115 mm
Dikte	54 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE