

Naaldhulslager NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nax6040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Shaft dia. mm	Identification number					
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g
60		NAX 6040Z	454	---	---	---

Boundary dimensions mm										Basic rolling diameter d ₂ Min. mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm
F _w	D	D ₁	D ₂	L	H	r _s min.	d ₁	Radial	Axial		Radial	Axial			
60	72	85	86.5	40	17	12	1	60	75	47 500	41 400	103 000	89 700	4 000	

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390376
Binnendiameter	60 mm
Buitendiameter	72 mm
Dikte	40 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE