

Naaldhulslager NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nbx6040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number													
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover	Mass (Ref.) g			
60	---		---		---		---		NBX 6040Z	538			
Boundary dimensions mm													
F_w	D	D_1	D_2	L	H	r_1 min.	d_f	Basic load rating C	Basic static load rating C_0		Allowable rotational speed ⁽²⁾		
60	72	85	86.5	40	17	12	1	60	47 500	64 600	103 000	224 000	4 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390529
Binnendiameter	60 mm
Buitendiameter	72 mm
Dikte	40 mm
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE