

Naaldhulslager NBX6040-IKO - NBX6040-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nbx6040-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number									
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
60	---	---	---	NBX 6040	501	---			
Boundary dimensions mm									
F_w	D	D_1	D_2	L	H	r_1	r_2 min.	d_f	Basic load ratings d_a
60	72	85	86.5	40	17	12	1	60	82
								Basic dynamic load rating C	
								Radial	47 500
								Axial	64 600
								Basic static load rating C_0	
								Radial	103 000
								Axial	224 000
								Allowable rotational speed ⁽²⁾	
									4 000

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390536
Binnendiameter	60 mm
Buitendiameter	72 mm
Dikte	40 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE