

Naaldhulslager NAXI723Z-IKO - NAXI723Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/naxi723z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number													
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g	d	D	D ₁	
	7		NAXI 723Z	45	—	—	—	—					
Boundary dimensions mm													
D ₂	L	B	H	I ₁	r ⁽¹⁾	r ⁽²⁾	r ⁽³⁾	d ₄	d ₅	d	Assembled inner ring		
25	23	16	9	6.5	0.3	0.2	10	10	18	9	8 230	10 000	
Basic dynamic load rating C										Basic static load rating C ₀		Allowable rotational speed ⁽⁴⁾ rpm	
Radial					Axial					Radial			Axial
N					N					N		N	
9 190										11 100		9 500	LRT 71016

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390574
Binnendiameter	7 mm
Buitendiameter	19 mm
Dikte	23 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE