

## Naaldhulslager NBXI1223Z-IKO - NBXI1223Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nbxi1223z-iko>

**LINEAR TYPE NEEDLE ROLLER BEARINGS**

Needle Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number														
Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover		Mass (Ref.) g		$d$		
---		---		---		<b>NBXI 1223Z</b>		63		12		12		
Boundary dimensions mm			Bore diameter mm		Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup>		Assemble			
$B$	$H$	$I_1$	$r_{max}$	$r_{min}$	$F_w$	$d_a$	$d_b$	Radial	Axial	Radial	Axial	rpm		
16.5	9	6.5	0.3	0.3	15	15	26	14	12 300	10 200	14 900	23 900	14 000	LRT 1

Minimum allowable value of chamfer dimension r  
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series.  
The outer ring has an oil groove and an oil hole.  
Grease is not prepacked. Perform proper lubrication.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390710
Binnendiameter	12 mm
Buitendiameter	24 mm
Dikte	23 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE