

Naaldhulslager NAXI1425Z-IKO - NAXI1425Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/naxi1425z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number										d	D	D _i	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover				
14		NAXI 1425Z	65.5	---	---	---	---	---	---	---	---	14	26	30

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
D ₂	L	B	H	I ₁	r _{max}	r _{min}	d ₄	d ₅	d		Radial	Axial			Radial	Axial
31	25	17	9	8	0.3	0.3	17	17	25	16	12 900	10 800	16 300	14 500	8 500	LRT 141717

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390734
Binnendiameter	14 mm
Buitendiameter	26 mm
Dikte	31 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE