

Naaldhulslager NAXI1730-IKO - NAXI1730-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/naxi1730-iko>

IICO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
17	NAXI 1730	99	—	—	—	—	17	30	35

Boundary dimensions mm				Bore chamfer radius mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring						
D ₂	L	B	H			Radial	Radial			Axial					
36	30	20.5	10	10.5	0.3	0.3	20	29	19	17 600	14 200	25 400	19 700	7 500	LRT 172020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remark: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390765
Binnendiameter	17 mm
Buitendiameter	30 mm
Dikte	30 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE