

# Naaldhulslager NAXI2530-IKO - NAXI2530-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/naxi2530-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
25	NAXI 2530	179	—	—	—	—	25	42	47

Boundary dimensions mm				Bore chamfer mm	Bore chamfer mm	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring						
D <sub>2</sub>	L	B	H			Radial	Axial	Radial	Axial								
48	30	20.5	11	9.5	0.6	0.3	30	40	25	100	20	400	40	100	33 600	6 500	LRT 253020

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390840
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	42 mm
Buitendiameter	1.654" inch
Dikte	30 mm
Dikte	1.181" inch
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE