

Naaldhulslager NBXI3532-IKO - NBXI3532-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nbxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

| Shaft dia. mm | Identification number | | | | | | d | D | D _i |
|------------------|-----------------------|-----------------|------------------|------------------|-----------------|------------------|----|----|----------------|
| | Mass (Ref.) g | With dust cover | Mass (Ref.) g | Mass (Ref.) g | With dust cover | Mass (Ref.) g | | | |
| 35 | --- | --- | --- | NBXI 3532 | 286 | --- | 35 | 52 | 60 |

| Boundary dimensions mm | | | Lead-in chamfer mm | Lead-in chamfer mm | Basic dynamic load rating C | Basic static load rating C ₀ | | Allowable rotational speed ⁽¹⁾ rpm | Assembled inner ring | | | | | | | |
|---------------------------|----|----|-----------------------|-----------------------|--------------------------------|--|--------|--|----------------------|--------|--------|--------|--------|---------|-------|------------|
| D ₂ | L | H | | | | Radial | Radial | | | Radial | Radial | | | | | |
| 61 | 32 | 20 | 13 | 10 | 0.6 | 0.3 | 40 | 40 | 57 | 39 | 29 400 | 41 700 | 54 100 | 133 000 | 6 000 | LRT 354020 |

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952390949 |
| Binnendiameter | 35 mm |
| Buitendiameter | 52 mm |
| Dikte | 32 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE