

Naaldhulslager NAXI4032Z-IKO - NAXI4032Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/naxi4032z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
40		NAXI 4032Z	324	---	---	---	40	58	65

Boundary dimensions mm				Bearing width mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 404520
D ₂	L	B	H			Radial	Radial		
66.5	32	20	14	9	31 000	27 900	60 200	55 100	5 000

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390970
Binnendiameter	40 mm
Buitendiameter	58 mm
Dikte	32 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE