

Naaldhulslager
NBXI4535Z-IKO - NBXI4535Z-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nbxi4535z-iko

IKO


COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing

With Inner Ring

Needle Roller Bearings with Thrust Roller Bearing

With Inner Ring



Shaft dia. mm	Identification number								d	D	D ₁	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover				
45	---	---	---	---	NBXI 4535Z				396	45	62	70

Boundary dimensions mm				Load ratings mm				Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 455025						
D ₂	L	B	H	I ₁	I ₂	d ₁	d ₂	Radial	Axial	Radial	Axial								
71.5	35	25	14	10	0.6	0.3	50	67	49	42	200	43	300	83	400	148	000	5	000

Notes⁽¹⁾

Minimum allowable value of chamfer dimension r

⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remark 1: The outer ring has an oil groove and an oil hole.

2: Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391038
Binnendiameter	45 mm
Buitendiameter	62 mm
Dikte	35 mm
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE